



FML - FML/SS

Forestry mulcher with swinging hammers rotor for tractors between 40 and 100 HP.

Standard equipment: PTO drive shaft, gearbox with freewheel, hydraulic rear hood.

Options: hydraulic top link, pushing frame.



FML

Model	Tractor HP		PTO rpm	Working width mm	Overall width mm	Weight Kg	Grinding diameter mm (max)	Teeth q.ty/type FML
	min	max						
FML 125	40	80	540 o 1000	1210	1590	820	200	20
FML 150	50	80	540 o 1000	1450	1830	885	200	24
FML 175	60	100	540 o 1000	1690	2070	950	200	28
FML 200	70	100	540 o 1000	1930	2310	1015	200	32

FML/SS with hydraulic side shifting

Model	Tractor HP		PTO rpm	Working width mm	Overall width mm	Weight Kg	Grinding diameter mm (max)	Teeth q.ty/type FML
	min	max						
FML/SS 150	50	80	540 o 1000	1450	1830	850	200	24
FML/SS 175	60	100	540 o 1000	1690	2070	1020	200	28
FML/SS 200	70	100	540 o 1000	1930	2310	1090	200	32

The weight refers to the machine without optinos.



Rotor type FML



Hammer Type FML



FML/S

Forestry mulcher with swinging hammers rotor for tractors between 60 and 130 HP.

Standard equipment: PTO drive shaft, gearbox with freewheel, hydraulic rear hood, adjustable skids.

Options: hydraulic top link, pushing frame, hydraulic pushing frame (only for FML/S 200 and 225), hammers with tungsten carbide tips FMM/HM.



FML/S

Model	Tractor HP min	Tractor HP max	PTO rpm	Working width mm	Overall width mm	Weight Kg	Grinding diameter mm (max)	Teeth q.ty/type FMM
FML/S 150	60	100	540 o 1000	1450	1830	970	250	24
FML/S 175	70	100	540 o 1000	1690	2070	1070	250	28
FML/S 200	80	130	1000	1930	2320	1220	250	32
FML/S 225	90	130	1000	2170	2560	1370	250	36

The weight refers to the machine without options.



Rotor type FML/S



Hammer Type FMM



Hammer type FMM/HM (Option)



FMM

Forestry mulcher with swinging hammers rotor for tractors between 80 and 160 HP.

Standard equipment: PTO drive shaft, gearbox with freewheel, hydraulic rear hood, adjustable skids.

Options: hydraulic top link, pushing frame, hydraulic pushing frame, hammers with tungsten carbide tips FMM/HM.



FMM

Model	Tractor HP min	Tractor HP max	PTO rpm	Working width mm	Overall width mm	Weight Kg	Grinding diameter mm (max)	Teeth q. ty/type FMM
FMM/ST 150	80	110	540 o 1000	1450	1930	1300	30	24
FMM/ST 175	90	110	540 o 1000	1690	2170	1390	30	28
FMM/ST 200	100	120	540 o 1000	1930	2410	1470	30	32
FMM/DT 200	100	160	1000	1930	2490	1650	30	32
FMM/DT 225	110	160	1000	2170	2730	1780	30	36
FMM/DT 250	120	160	1000	2410	2970	1920	30	40

The weight refers to the machine without options.



Rotor type FMM



Hammer Type FMM



Hammer type FMM/HM (Option)