



## STCL/R

Stone crushers for tractors between 80 and 180 HP with a max working depth of 15 cm.

**Standard equipment:** single or double driven transmission (depending from the model), PTO drive shaft with cam clutch, gearbox with free wheel, penetration skids, hydraulic rear hood, adjustable counter knives, adjustable three point linkage. Possibility to choose between 540 or 1000 rpm gearbox (only for models with single driven transmission).

**Options:** dosing blade, road kit, hydraulic top link.

**Notes:** For their correct usage, a creeper gear transmission is recommended.



## STCL/R

Modello	Tractor HP Min - Max	PTO rpm	Working Width mm	Overall Width mm	Weight Kg	Grinding diameter mm(max)	Working Depth mm (max)	Teeth q.ty type STCL
STCL/R 125	80 - 120	540 o 1000	1350	1654	1280	150	150	28
STCL/R 150	90 - 120	540 o 1000	1590	1894	1435	150	150	34
STCL/R 175	100 - 120	540 o 1000	1830	2134	1570	150	150	38
STCL/R/DT 175	100 - 180	1000	1830	2134	1600	150	150	38
STCL/R/DT 200	120 - 180	1000	2070	2374	1745	150	150	42

*The data refers to the machine without options.*



Rotor type STCL



Tooth type STCL