

NEW

ROAD PLANERS FOR SKID STEERS

RWM/SSL

Disc road planer for skid steers.

The RWM/SSL is a disc-type road planer for skid steers from 75 to 120 hp, able to shred channels up to 50 cm deep with modular widths of 8, 10 or 12 cm. The RWM/SSL aims mainly to ensure extremely precise excavations for laying electrical, water, gas and fiber optic conduits. The depth indicator allows precise

depth management and the self-leveling penetration skids allow the working depth to be kept constant at all times. The optimized side output allows the track to be kept free of waste materials at all times.



75-120 hp



Depth 50 cm



Depth Indicator
for precise depth control



Self-leveling skids
with hydraulic depth control




Hydraulic drive system
for accurate positioning over the work area




Modular cutting discs
of 3, 4 or 5 inches

MAIN OPTIONS



Cutting disc available in three widths



WSS Basic water injection system
to reduce dust and cool the teeth



Wiring adaptors
Wiring adaptors interface to allows a Plug & Play coupling with the most popular skid steers

STANDARD EQUIPMENT

| | |
|---|--|
| Hydraulic working depth adjustment | Anti-shock block valve with relief and anticavitation valves |
| Hydraulic side shifting | Hydraulic hoses for connections |
| Mobile sides-frame | Interchangeable Hardox® antiwear skids plate |
| Enclosed / anti-dust machine body | Disc rotor with interchangeable sectors |
| Working pressure control gauge | Diverter valve 12 V |
| 1500 cc fixed displacement hydraulic piston motor | Supporting service leg |
| Direct drive motor transmission | |

OPTIONS

| | |
|-----------------------------------|----------------|
| Multiple disc rotor width options | Adaptor wiring |
| Water spray system WSS Basic | |

MODEL

RWM/SSL

| | 80 mm Disc Rotor STD | 100 mm Disc Rotor OPT | 120 mm Disc Rotor OPT |
|----------------------------------|----------------------|-----------------------|-----------------------|
| Engine (hp) | 75-120 | 75-120 | 75-120 |
| Requirements Flow (L/min) | 120-150 | 120-150 | 120-150 |
| Pressure (bar) | 200-350 | 200-350 | 200-350 |
| Working width (mm) | 80 | 100 | 120 |
| Total width (mm) | 1640 | 1640 | 1640 |
| Weight (kg) | 1315 | 1340 | 1365 |
| Working depth (mm) | 250-500 | 250-500 | 250-500 |
| Rotor diameter (mm) | 1400 | 1400 | 1400 |
| Side shifting (mm) | 560 | 560 | 560 |
| N° teeth type R | 40 | 50 | 55 |

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

ROTOR TYPE R



R 44/C
(optional)