FORESTRY MULCHERS **UMH/MEGA**

Forestry mulcher for PTO tractors with fixed tooth rotor.

UMH/MEGA is a unique forestry mulcher. It is designed highly productive mulcher combined with an for the most powerful tractors available, and allows you to work large areas in a quick and effective way. The UMH/MEGA was built for operators seeking a

extremely efficient tiller. It can mulch trees up to 50 cm diameter and grind at a depth of 25 cm, all in one machine.

> Z style self-ranging system for the PTO drive shaft/gearbox helps keep the correct operating angle between the PTO shaft and the power take-off





Aggressive body design the protruding rotor allows more material to process without dragging

Inner anti wear clad plates FCP absorbs wear while protecting the frame



Standard hydraulic clutch transmission protects the transmission at PTO engagement for smooth starting and improves machine performance

Adjustable extended 3 point hitch fits perfectly with any type of tractor

Side transmission with belts in Poly-Chain® Carbon for longer lasting performance



MAIN OPTIONS



Hydraulically adjustable skids allow the rotor to penetrate deeply into the soil for grinding stumps and roots



W style self aligning device between PTO drive shaft/gearbox allows the mulcher to work at several angles without damaging the PTO



Mechanical/hydraulic push frame guides and pushes material away from carrier



Additional ripper for push frame helps with the positioning of standing material while mulching



STANDARD EQUIPMENT

Hydraulic rear hood	Hydraulic clutch transmission	
Inner anti wear clad plates FCP	Gearbox with freewheel	
Adjustable extended 3 point linkage	Gearbox with oil cooling system	
Enclosed machine body	PTO shaft	
Centralized greasing hub	Bolted-on rotor shafts (in forged	
Hydraulic hoses integrated in the frame	Hydraulic top link	
Cylinder protection	Z style self ranging system of th	
Inside lateral protection	Forged and hardened interchar	
Dual row protection chains	Third row of interchangeable for	
Poly-Chain® belts transmission		

OPTIONS

Multiple tooth options	Mechanical guard frame	
W style self aligning device between PTO drive shaft/gearbox	Hydraulic guard frame	
Hydraulically adjustable skids	Extra ripper for push frame	
Special skids to go underground		
MODEL	UMH/MEGA 225	UMH/MEGA 250
Tractor (hp)	350-500	350-500
PTO (rpm)	1000	1000
Working width (mm)	2320	2560
Total width (mm)	2820	3060
Weight (kg)	5970	6320
Rotor diameter (mm)	910	910
Max shredding diameter (mm)	500	500
Max working depth (mm)	250	250
No. teeth type A/3+MH	94+2	106+2

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

(option)

ROTOR TYPE A





TOOTH A/3 TOOTH A/3/HD (standard)

тоотн мн (side scraper)



- m
- ed steel)
- the PTO drive shaft/gearbox
- angeable counter-blades
- orged and hardened counter-blades