


FORESTRY TILLERS

SSL/SPEED

Tiller for tractors from 110 to 220 hp.

A Forestry Tiller designed to meet the needs of professionals who require both surface clearing and soil reclamation. This machine allows you to clean up crop residue and grind trees and stumps up to 30 cm diameter and 30 cm deep.

The optional push frame mounts to the support roller, while adjustable counter-blades are used to manually control the final product size.



Adjustable counter-blade for longer working life



Dual transmission with side gearbox increase power delivery to the rotor



MAIN OPTIONS



Hydraulic controlled roller helps with compaction and working uneven terrain



Hydraulic top link

STANDARD EQUIPMENT

Hydraulic rear hood	Friction clutches (SSL/SPEED/DT)
Enclosed machine body	PTO shaft with cam clutch
Inside lateral protection	Bolted-on rotor shafts (in forged steel)
Protection chains	Welded steel counter-blades
Transmission with side gearbox	Adjustable counter-blade (forest)
Gearbox with freewheel	

OPTIONS

Multiple tooth options	Hydraulic guard frame
Hydraulic top link	Hydraulic support roller

MODEL	SSL/SPEED-150	SSL/SPEED-175	SSL/SPEED/DT-200	SSL/SPEED/DT-225	SSL/SPEED/DT-250
Tractor (hp)	110-160	110-160	120-220	130-220	140-220
PTO (rpm)	1000	1000	1000	1000	1000
Working width (mm)	1600	1840	2080	2320	2560
Total width (mm)	1920	2160	2400	2640	2880
Weight (kg)	2000	2160	2600	2810	3030
Rotor diameter (mm)	600	600	600	600	600
Max shredding diameter (mm)	300	300	300	300	300
Max working depth (mm)	300	300	300	300	300
No. teeth type B/3+C/3/SS	44+4	50+4	58+4	66+4	74+4

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

ROTOR TYPE B



TOOTH B/3 (standard)



TOOTH B/3/HD (option)



TOOTH G/3 (option)



TOOTH G/3/HD (option)



TOOTH C/3/SS (side scraper)