

MULTITASKS

MTL

Multitask for tractors from 140 to 300 hp.

The MTL enables soil stabilization, asphalt and rock slab shredding, and stone crushing, down to a maximum operating depth of 28 cm. The variable-geometry grinding chamber, adjustable grille on the hood, and adjustable Hardox counter blade consistently enable optimal crushing results. Internal protection plates on the frame, bolted both centrally and laterally, ensure the head is robust and reliable

while also guaranteeing excellent resistance to wear. The handy depth indicator allows you to check the operating level directly from the cab, and the central gearbox with universal-joint alignment system is designed to be compatible with a wide range of tractors on the market. The head comes standard with G/3 teeth, with the option of G/3/HD teeth and R/65 or R/65/HD picks on a dedicated rotor.




140-300 hp



Depth 28 cm max



Variable displacement chamber



STANDARD EQUIPMENT

Hydraulically adjustable rear hood	Transmission with side gearbox
Interchangeable wear-resistant Hardox® plates	Freewheel gearbox
Enclosed, dust-resistant machine body	Side PTO shafts with friction clutches
Variable displacement chamber	Central PTO shaft with cam clutch
Adjustable hood grille	Interchangeable forged steel rotor shafts
Wear-resistant side plates	Adjustable Hardox® counter blade
Bolt-on interchangeable protection chains	Dozing blades with spring system
FCP wear-resistant clad plates	PTO shaft support for machine at rest

OPTIONS

Multiple tooth options	Basic WSS - water spray system
Hydraulic top link cylinder	High Flow WSS - water spray system

MODEL	MTL-150	MTL-175	MTL-200	MTL-225	MTL-250
Tractor (hp)	140-240	150-240	160-300	170-300	180-300
PTO (rpm)	1000	1000	1000	1000	1000
Working width (mm)	1480	1720	1960	2200	2440
Total width (mm)	1820	2060	2300	2540	2780
Weight (Kg)	3370	3620	3870	4120	4370
Rotor diameter (mm)	595	595	595	595	595
ROTOR G/3	Working depth (mm) (Max. 1-Max. 2)	150-280	150-280	150-280	150-280
	No. teeth type G/3+STC/3/FP	42+6	50+6	60+6	70+6
ROTOR/65 (optional)	Rotor diameter (mm)	612	612	612	612
	Working depth (mm) (Max. 1-Max. 2)	150-280	150-280	150-280	150-280
	No. picks type R/65+R/65/HD	98+16	114+16	138+16	154+16

Max. 1: with rotor only **Max. 2:** maximum depth (maximum working depth depending on ground conditions).
This information refers to the machine equipped as standard. The technical data in this catalogue may be altered without prior notice.

MAIN OPTIONS



Hydraulic top link



Multiple tooth options



The **Water Spray System** (Basic & High Flow) has the dual function of cooling and mixing

ROTOR TYPE G



TOOTH G/3 (standard)



TOOTH G/3/HD (option)



ADAPTOR G/3 WITH PICK R/44 (option)



TOOTH STC/3/FP (side scraper)

ROTOR TYPE R



PICK R/65 (standard)



PICK R/65/HD (option)



ADAPTOR R/65 WITH PICK R/44 (option)



PICK R/65/HD (side scraper)