STUMP CUTTERS FOR EXCAVATORS

SCM/EX

Stump cutter for excavators from 14 to 24 t.

The SCM/EX is designed to remove stumps quickly and easily. The front hood with hydraulic adjustment and front fixed thumb are designed to shift previously cut material. This feature combined with the reliability and resistance of the disc allows for the best performance and safety while the stumps are being removed.

130-185 L/min

14-24 t

Access panel

VT motor
to increase performance
and reduce operating costs

Front hydraulic hood with bolt-on chains/protection plates

Motor enclosed in frame
protected from dirt and damage

Adjustable supporting service stand
for storing the machine when not in use

STANDARD EQUIPMENT

160/108cc variable torque hydraulic piston motor	Bulkhead for hydraulic connections
Flow control system valve	Hydraulic front hood
Safety and anticavitation valve	Screwed protection chains
Enclosed / anti dust machine body	Bolt-on chains / protection plates
Motor enclosed in the frame	Supporting service leg
Poly Chain® belt transmission	

OPTIONS

Customized setting hydraulic motor	Customized attachment bracket with pins
Diverter valve (plug & play)	Customized attachment bracket with pins and leg
Front fixed thumb bracked	

MODEL	SCM/EX/VT
Flow rate (L/min)	130-185
Pressure (bar)	220-350
Excavator weight (t)	14-24
Total width (mm)	780
Weight (kg)	1100
Rotor diameter (mm)	815
No. teeth type M/1+M/2+M/3+M/4	12+3+12+3

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

MAIN OPTIONS

Front fixed thumb

Customized setting hydraulic motor



Customized attachment bracket with fixed thumb

Customized attachment bracket

DISC ROTOR

TOOTH M/3
(standard)

TOOTH M/1
(standard)

TOOTH M/4
(standard)

TOOTH M/2
(standard)