FORESTRY MULCHERS FOR EXCAVATORS

BL5/EX/VT - BL5/EX/SONIC

The mulcher for the largest excavators, with Bite Limiter technology.

The BL5/EX for 24-36 ton excavators, mulches vegetation up to 40 cm in diameter and has a working width of 160 cm. This head is ideal for handling and removing vegetation in wooded areas, especially when optimizes fuel consumption and ensures excellent a large shredding capacity and fast operational speed is required. The rotor with Bite Limiter technology

comes with special wear-resistant steel limiters that limit the teeth's reach. This cuts down on power demand, promotes a consistent working speed, performance when mulching any kind of wood.



adjustable motor to obtain the maximum performance out of any excavator



Diverter valve for hydraulic control of the hood



Poly-Chain® belt drive transmission optimal power transfer



Sonic System

is a new automatic intelligent system that manages the hydraulic transmission. It makes the mulching machine to perform at the maximum capacityin all conditions (BL5/EX/SONIC)





Spike PRO counter-blades

for finer mulched material

Rotor with Bite Limiter technology

maximum productivity using the least amount of power

MAIN OPTIONS



Thumb bracket with hydraulic thumb for handling material





180-300 L/min



Ø 40 cm max



24-36 t



STANDARD EQUIPMENT

160/108cc variable torque hydraulic piston motor (180-300 L/min) (BL5/EX/VT)	Hydraulic front hood	
160cc variable torque hydraulic piston motor (180-300 L/min) (BL5/EX/SONIC)	Dedicated rear hood (deflector)	
Flow control system valve	Adjustable skids	
Diverter valve	Additional reinforced side plates	
Safety and anticavitation valve	Front fixed thumb bracked	
Enclosed / anti dust machine body	Spike Pro counter-blade	
Motor enclosed in the frame	Rotor Bite Limiter	
Poly Chain® Belt Transmission	Sonic System (BL5/EX/SONIC)	
Bulkhead for hydraulic connections		

OPTIONS

Customized setting hydraulic motor (BL5/EX/VT)	Hydraulic thumb
Hydraulic front hood for excavator AUX line (BL5/EX/VT)	Customized attachment bracket with pins

BL5/EX/VT* 150	BL5/EX/SONIC 150
180-300	180-300
240-350	240-350
24-36	24-36
1584	1584
2375	2375
517	517
400	400
28	28
	180-300 240-350 24-36 1584 2375 517 400

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice. *Variable displacement hydraulic motor.

ROTOR TYPE BL



BLADE BL/MAX