

## FORESTRY TILLERS

# SSL SPEED

### Forestry tiller for PTO tractors with fixed teeth rotor.

A Forestry Tiller designed to meet the needs of professionals who require both surface clearing and soil reclamation. This machine allows you to clean up crop residue and grind trees and stumps up to 30 cm diameter and 30 cm deep.

The optional push frame mounts to the support roller, while adjustable counter-blades are used to manually control the final product size.



100-220 hp



Ø 30 cm max



Depth 30 cm



Adjustable counter-blade  
for longer working life



Dual transmission with  
side gearbox  
increase power delivery  
to the rotor



#### STANDARD EQUIPMENT

Hydraulic rear hood	Friction clutches (SSL/DT SPEED)
Enclosed machine body	PTO shaft with cam clutch
Inside lateral protection	Bolted-on rotor shafts (in forged steel)
Protection chains	Welded steel counter-blades
Transmission with side gearbox	Adjustable counter-blade (forest)
Gearbox with freewheel	

#### OPTIONS

Multiple tooth options	Hydraulic guard frame
Hydraulic top link	Hydraulic support roller

MODEL	SSL SPEED 150	SSL SPEED 175	SSL/DT SPEED 200	SSL/DT SPEED 225	SSL/DT SPEED 250
<b>Tractor (hp)</b>	100-160	110-160	120-220	130-220	140-220
<b>PTO (rpm)</b>	1000	1000	1000	1000	1000
<b>Working width (mm)</b>	1600	1840	2080	2320	2560
<b>Total width (mm)</b>	1920	2160	2400	2640	2880
<b>Weight (kg)</b>	2000	2160	2600	2810	3030
<b>Rotor diameter (mm)</b>	600	600	600	600	600
<b>Max shredding diameter (mm)</b>	300	300	300	300	300
<b>Max working depth (mm)</b>	300	300	300	300	300
<b>No. teeth type B/3+C/3/SS</b>	44+4	50+4	58+4	66+4	74+4

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

#### MAIN OPTIONS



Hydraulic controlled roller  
helps with compaction  
and working uneven terrain



Hydraulic top link

#### ROTOR TYPE B



TOOTH B/3  
(standard)



TOOTH B/3/HD  
(option)



TOOTH G/3  
(option)



TOOTH G/3/HD  
(option)



TOOTH C/3/SS  
(side scraper)