ROAD PLANERS FOR SKID STEERS

RPL/SSL

Fixed tooth road planer for skid steers up to 135 hp.

The RPL/SSL is a road planer for skid steers from 60 to 135 hp, capable of milling up to 17 cm deep and is available in three widths of 45, 60 and 75 cm.

The RPL/SSL is ideal for road preparation before ading a new layer of asphalt or concrete, or to simplify excavation operations. Self-leveling skids

and tilt ensure optimal results. Operational precision is ensured by the hydraulic drive system as well as practical depth and cutting indicators. The line is completed with teeth specifically designed for asphalt and concrete road surfaces.



Cutting and depth indicators for precise operation control



Tilt

for optimal results on uneven surfaces

Hydraulic drive system

for accurate positioning over the work area

Self-leveling skids

With independent hydraulic position control

MAIN OPTIONS



Teeth for working on concrete



WSS Basic water injection system to reduce dust and cool the



Wiring adaptors
Wiring adaptors interface
to allows a Plug & Play
coupling with the most
popular skid steers



STANDARD EQUIPMENT

Mechanical floating tilt system (tilt)	Anti-shock block valve with relief and anti-cavitation valves	
Independent hydraulic skids control	Hydraulic hoses for connections	
Mobile sides-frame	Interchangeable Hardox® antiwear skids plate	
Hydraulic side shifting	Asphalt round bit teeth	
Enclosed / anti-dust machine body	Cutting indicator	
Working pressure control gauge	Diverter valve 12 V	
860 cc fixed displacement hydraulic piston motor (RPL/SSL 45-60)	940 cc fixed displacement hydraulic piston motor (RPL/SSL 75)	
Direct drive motor transmission		

OPTIONS

Multiple tooth options	Adaptor wiring
Water spray system WSS Basic	SAE attachment frame with integrated water tank
Roof mounted water tank kit for skid steer	

MODEL	RPL/SSL 45	RPL/SSL 60	RPL/SSL 75
Engine (hp)	60-110	60-110	90-135
Requirements Flow (L/min)	100-155	100-155	120-170
Pressure (bar)	180-350	180-350	180-350
Working width (mm)	450	600	750
Total width (mm)	1650	1650	1650
Weight (kg)	900	950	1000
Working depth (mm)	0-170	0-170	0-170
Rotor diameter (mm)	600	600	600
Tilting angle ±	8°	8°	8°
Side shifting (mm)	560	560	560
N° picks type R	42	54	60

 ${\it Data\ refers\ to\ machine\ as\ standard.}\ The\ technical\ data\ in\ this\ catalogue\ may\ be\ altered\ without\ prior\ notice.$

ROTOR TYPE R





PICK R/44/A (standard)

PICK R/44/C