FORESTRY MULCHERS FOR EXCAVATORS

BL1/EX - BL1/EX/VT

Forestry mulcher with Bite Limiter technology for excavators up to 7.5 tons.

shred light vegetation, shrubs and trees up to 12 cm in diameter. The Bite Limiter technology on this head is ideal for high productivity in managing vegetation, with C/3/MINI teeth.

The BL1/EX forestry mulcher for 4-7.5 ton excavators can reliably efficient shredding. The head is available in the VT version and in the no-drain fixed gear motor version. The BL1/EX can be equipped with BL/MINI blades and



Hydraulic front trap door helps contain debris and achieves finer sizing (optional)

Hydraulic piston motor with automatic variable displacement (BL1/EX/VT)

> Gear motor with no-drain fixed displacement (BL1/EX)

Custom made thumb bracket to move and reposition material



Dedicated rear hood (deflector) controls mulched material output for greater safety



Bite Limiter rotor special steel limiter rings control the depth of cut





Attachment bracket



Excavator stand and thumb bracket useful in moving material to be mulched



Hydraulic front hood



STANDARD EQUIPMENT

25cc hydraulic gear motor (60-90L/min) (BL1/EX)	Belt transmission
55/38 cc variable torque hydraulic piston motor (65-140 L/min) (BL1/EX/VT)	Bulkhead for hydraul
Flow control system valve	Front hood with mec
Safety and anticavitation valve	Rotor Bite Limiter
Enclosed / anti dust machine body	Dedicated rear hood
Motor enclosed in the frame	

OPTIONS

Customized setting hydraulic motor	F
Diverter valve	С
Hydraulic front hood	Ν
Hydraulic front hood for excavator AUX line	

MODEL	BL1/EX-75	BL1/EX/VT-75
Flow rate (L/min)	60-90	65-140
Pressure (bar)	180-250	180-350
Excavator weight (t)	4,5-7,5	4-7,5
Working width (mm)	800	800
Weight (kg)	385	390
Rotor diameter (mm)	310	310
Max shredding diameter (mm)	120	120
No. blades type BL/MINI	14	14

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

ROTOR TYPE BL



TOOTH C/3/MINI

BLADE BL/MINI (standard)

(option)

ulic connections

echanical adjustment

(deflector)

Front fixed thumb bracked

Customized attachment bracket with pins

Multiple tooth options