

WHEEL SAWS FOR SKID STEERS

RWM/SSL

Wheel saw for skid steers.

The RWM/SSL is a wheel saw for skid steers from 75 to 135 hp, able to shred channels up to 50 cm deep with modular widths of 8, 10 or 12 cm. The RWM/SSL aims mainly to ensure extremely precise excavations for laying electrical, water, gas and fiber optic conduits. The depth indicator allows precise depth

management and the self-leveling skids allow the working depth to be kept constant at all times. The optimized side output allows the track to be kept free of waste materials at all times.



75-135 hp



Depth
50 cm



Hydraulic drive system
for accurate positioning over the work area

Depth Indicator
for precise depth control




Self-leveling skids
with hydraulic depth control



Modular cutting discs
of 3, 4 or 5 cm

MAIN OPTIONS



Cutting disc available in three widths



WSS Basic water injection system
to reduce dust and cool the teeth



Wiring adaptors
Wiring adaptors interface to allow a Plug & Play coupling with the most popular skid steers

STANDARD EQUIPMENT

Hydraulic working depth adjustment	Anti-shock block valve with relief and anticavitation valves
Hydraulic side shifting	Hydraulic hoses for connections
Mobile sides-frame	Interchangeable Hardox® antiwear skids plate
Enclosed / anti-dust machine body	Disc rotor with interchangeable sectors
Working pressure control gauge	Diverter valve 12 V
1500 cc fixed displacement hydraulic piston motor	Supporting service leg
Direct drive motor transmission	

OPTIONS

Multiple disc rotor width options	Adaptor wiring
Water spray system WSS Basic	Roof mounted water tank kit for skid steer

MODEL

RWM/SSL

	80 mm Disc Rotor STD	100 mm Disc Rotor OPT	120 mm Disc Rotor OPT
Engine (hp)	75-135	75-135	75-135
Requirements Flow (L/min)	120-170	120-170	120-170
Pressure (bar)	200-350	200-350	200-350
Working width (mm)	80	100	120
Total width (mm)	1640	1640	1640
Weight (kg)	1315	1340	1365
Working depth (mm)	250-500	250-500	250-500
Rotor diameter (mm)	1400	1400	1400
Side shifting (mm)	560	560	560
N° picks type R	40	50	55

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

ROTOR TYPE R



PICK R/44/C
(optional)