

STONE CRUSHERS

RSH/HP

FAE’s top-of-the-line stone crushers.

RSH/HP is FAE’s most advanced stone crusher. It is suiting for crushing slabs of rock and stones up to 50 cm in diameter and 50 cm deep. It works with 360-500 hp tractors and has a working width of 210-260 cm. RSH/HP is made for difficult farmland clearing work in places where large rocks and stones need to be cleared to prepare the field for agricultural use.

Its wide opening guides large material towards the rotor and, in combination with the adjustable counterblade, helps maintain consistently high performance when working the soil.



360-500 hp



Ø 50 cm max (stones)



Depth 50 cm



Structural frame in steel  
maximum strength and durability  
in heavy duty operations



Side reduction gears and central  
gearbox with oilcooling system  
maximum productivity and efficiency  
maintained in all workingconditions



Wide opening  
to efficiently process more material

MAIN OPTIONS



Rear hood grill  
allows larger material to be  
held back and crushed again  
for optimum results



Adjustable steel  
dosing blade  
perfect distribution  
of the crushed material



Hydraulic top link  
precise control over operations

STANDARD EQUIPMENT

Hydraulic rear hood	Gearbox with freewheel
Interchangeable inner antiwear plates in Hardox®	Gearbox with oil cooling system
Enclosed machine body	PTO shaft
Inside lateral protection	Friction clutches
Protection chains	Bolted-on rotor shafts (in forged steel)
Transmission with side gearbox	Adjustable Hardox® counter-blade
Side gearbox with oil cooling system	Penetration skids

OPTIONS

Bolted grid on rear hood	Hydraulic top link
Multiple tooth options	Dozing blade

MODEL	RSH/HP 200	RSH/HP 225	RSH/HP 250
	Tractor (hp)	360-500	360-500
	PTO (rpm)	1000	1000
	Working width (mm)	2107	2347
	Total width (mm)	2670	2910
	Weight (kg)	7050	7450
	Max shredding diameter (mm)	500	500
ROTOR G/3	Rotor diameter (mm)	1115	1115
	Working depth (Max. 1-Max.2)(mm)	360-500	360-500
	No. teeth type G/3	104	116
	type STC/3/FP+STC/FP	4+4	4+4
ROTOR R	Rotor diameter (mm)	1065	1065
	Working depth (Max. 1-Max.2)(mm)	345-500	345-500
	No. teeth/picks type R/65+R/65/HD	138+24	160+24
	type STC/3/FP+STC/FP	6+6	6+6

Max. 1: with rotor only Max. 2: maximum depth (maximum working depth depending on ground conditions).  
Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

ROTOR TYPE G



TOOTH G/3  
(standard)



TOOTH G/3/HD  
(option)

ROTOR TYPE R



PICK R/65  
(option)



PICK R/65/HD  
(option)



TOOTH STC/3/FP  
(side scraper)



TOOTH STC/FP  
(side scraper)