

## WHEEL SAWS FOR SKID STEERS

# RWM/SSL

## Disc road planer for skid steers.

The RWM/SSL is a disc-type road planer for skid steers from 75 to 135 hp, able to shred channels up to 20 in deep with modular widths of 3.2, 4 or 4.7 inches. The RWM/SSL aims mainly to ensure extremely precise excavations for laying electrical, water, gas and fiber

optic conduits. The depth indicator allows precise depth management and the self-leveling penetration skids allow the working depth to be kept constant at all times. The optimized side output allows the track to be kept free of waste materials at all times.



75-135 hp



Depth  
20 in



**Hydraulic side shifting**  
for accurate positioning over the work area



**Modular cutting discs**  
of 3.2, 4 or 4.7 inches


**Depth Indicator**  
for precise depth control



**Self-leveling skids**  
with hydraulic depth control



## MAIN OPTIONS



**Cutting disc available in three widths**



**WSS Basic water injection system**  
to reduce dust and cool the teeth



**Wiring adaptors**  
Wiring adaptors interface to allow a Plug & Play coupling with the most popular skid steers

## STANDARD EQUIPMENT

Hydraulic working depth adjustment	Anti-shock block valve with relief and anticavitation valves
Hydraulic side shifting	Hydraulic hoses for connections
Mobile sides-frame	Interchangeable Hardox® antiwear skids plate
Enclosed / anti-dust machine body	Disc rotor with interchangeable sectors
Working pressure control gauge	Diverter valve 12 V
1500 cc fixed displacement hydraulic piston motor	Supporting service leg
Direct drive motor transmission	

## OPTIONS

Multiple disc rotor width options	Adaptor wiring
Water spray system WSS Basic	Roof mounted water tank kit for skid steer

## MODELLO

	RWM/SSL		
	80 mm Disc Rotor STD	100 mm Disc Rotor OPT	120 mm Disc Rotor OPT
<b>Engine</b> (hp)	75-135	75-135	75-135
<b>Requirements Flow</b> (gal/min)	32-45	32-45	32-45
<b>Pressure</b> (PSI)	2900-5080	2900-5080	2900-5080
<b>Working width</b> (in)	3.2	4	4.7
<b>Total width</b> (in)	65	65	65
<b>Weight</b> (lbs)	2900	2960	3010
<b>Working depth</b> (in)	10-20	10-20	10-20
<b>Rotor diameter</b> (in)	55	55	55
<b>Side shifting</b> (in)	22	22	22
<b>N° picks</b> type R	40	50	55

*Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.*

## ROTOR TYPE R



**PICK R/44/C**  
(standard)