


STUMP CUTTERS FOR EXCAVATORS

SCL/EX/VT

Disc stump cutters for excavators.

The SCL/EX/VT is for excavators ranging from 7 to 15 t. Thanks to the heavy duty and larger disk, stump removal is made easier in any situation;

even when using medium and small size excavators. This unit is compact, high performing and is equipped with a hydraulic door to control the exit of debris.

 105-170 L/min

 7-15 t



Access panel

VT motor

adjustable motor to obtain the maximum performance from any excavator, protected from dirt and damage



Front hydraulic hood with bolt-on chains

Motor enclosed in frame protected from dirt and damage



Adjustable supporting service stand for storing the machine when not in use

STANDARD EQUIPMENT

110/60cc variable torque hydraulic piston motor (105-170 L/min)	Poly Chain® belt transmission
Flow control system valve	Bulkhead for hydraulic connections
Safety and anticavitation valve	Hydraulic front hood
Enclosed / anti dust machine body	Screwed protection chains
Motor enclosed in the frame	Supporting service leg

OPTIONS

80/50cc variable torque hydraulic piston motor (75-120 L/min)	Front fixed thumb bracked
Customized setting hydraulic motor	Customized attachment bracket with pins
Diverter valve (plug & play)	Customized attachment bracket with pins and leg

MODEL


	SCL/EX/VT
Flow rate (L/min)	105-170
Pressure (bar)	180-350
Excavator weight (t)	7-15
Total width (mm)	902
Weight (kg)	755
Rotor diameter (mm)	660
No. teeth type L/1+L/2	15+15

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

MAIN OPTIONS



Front fixed thumb



Customized setting hydraulic motor



Customized attachment bracket with fixed thumb



Customized attachment bracket

DISC ROTOR



TOOTH L/1 (standard)



TOOTH L/2 (standard)