## NEW

# FORESTRY MULCHERS FOR EXCAVATORS

**BLO/EX** 

# Forestry mulcher with Bite Limiter technology for excavators up to 4 tons.

The BLO/EX forestry mulcher for 2-4 ton excavators can shred material up to 8 cm in diameter. Bite Limiter technology is ideal for high productivity vegetation management, designed with reliable and efficient shredding and easy maintenance in mind.

The BLO/EX's Direct Drive motor minimizes maintenance and makes it possible to have an extremely compact machine body. The BLO/EX can be equipped with BL/MINI blades and C/3/MINI teeth.



**Direct Drive Motor** for less maintenance and reduced size

**Rotor Bite Limiter** special steel profiles limit the blades' reach and optimize productivity

Adjustable rear deflector controls mulched material output for greater safety

## MAIN OPTIONS



**Customized attachment** bracket kit with customized pins



Attachment plate with self-leveling device (optional) adapts to all types of terrain

in the motor

Fixed thumb bracket built into the frame useful for moving materials that need to be mulched





### STANDARD EQUIPMENT

11 cc-gear hydraulic motor (BLO/EX 50)

16 cc-gear hydraulic motor (BL0/EX 75)

Flow Control system valve with integrated safety and anticavitation valves

Enclosed, dust-resistant machine body

Motor enclosed in the frame

Hydraulic hoses

#### OPTIONS

Customized attachment bracket kit with customized pins

Attachment plate with self-leveling device

16 cc-gear hydraulic motor (BL0/EX 50)

| MODEL                       | BL0/EX 50 | BL0/EX 75 |
|-----------------------------|-----------|-----------|
| Flow rate (gal/min)         | 8-18      | 8-18      |
| Pressure (PSI)              | 2600-3600 | 2600-3600 |
| Excavator weight (t)        | 2-4       | 3-4       |
| Working width (in)          | 22        | 31        |
| Total width (in)            | 40        | 49        |
| Weight (lbs)                | 470       | 553       |
| Rotor diameter (in)         | 12        | 12        |
| Max shredding diameter (in) | 3         | 3         |
| No. blades type BL/MINI     | 10        | 14        |
| No. tooth type C/3/MINI     | 10        | 14        |
|                             |           |           |

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.





**BLADE BL MINI** (standard)

(option)



| Deflector                                    |
|--|
| Thumb bracket                                |
| Direct-drive transmission                    |
| Interchangeable forged steel rotor shafts    |
| Bite Limiter Rotor                           |
| Wear-resistant interchangeable Hardox® soles |
|  |
|  |

| 11 cc-gear hydraulic motor (BL0/EX 75) |
|--|
| Multiple tooth options                 |
|  |