## FORESTRY MULCHERS FOR EXCAVATORS

# **BL1/EX - BL1/EX/VT**

# Forestry mulcher with Bite Limiter technology for excavators up to 7.5 tons.

The BL1/EX forestry mulcher for 4-7.5 ton excavators can shred light vegetation, shrubs and trees up to 5 inches in diameter. The Bite Limiter technology on this head is ideal for high productivity in managing vegetation, with

reliably efficient shredding. The head is available in the VT version and in the no-drain fixed gear motor version. The BL1/EX can be equipped with BL/MINI blades and C/3/MINI teeth.



Custom made thumb bracket to move and reposition material



Dedicated rear hood (deflector) controls mulched material output for greater safety



Bite Limiter rotor special steel limiter rings control the depth of cut

## MAIN OPTIONS



Attachment bracket



**Excavator stand and thumb** bracket useful in moving material to be mulched



Hydraulic front hood for optimal mulching, reduces the ejection of mulched material



### STANDARD EQUIPMENT

25cc hydraulic gear motor (60-90L/min) (BL1/EX)	
55/38 cc variable torque hydraulic piston motor (17-37 gpm) (BL1/EX/VT)	
Flow control system valve	
Safety and anticavitation valve	
Enclosed / anti dust machine body	
Motor enclosed in the frame	

#### OPTIONS

Customized setting hydraulic motor
Diverter valve
Hydraulic rear hood
Hydraulic front hood for excavator AUX line
Not supplied with hoses
MODEL
Flow rate (gal/min)
Pressure (PSI)
Excavator weight (t)

Working width (in)

Weight (lbs)

Rotor diameter (in)

Max shredding diameter (in)

No. blades type BL/MINI

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

#### **ROTOR TYPE BL**





**BLADE BL/MINI** (standard)

TOOTH C/3/MINI (option)

with automatic variable displacement (BL1/EX/VT)

with no-drain fixed displacement (BL1/EX)

Hydraulic front trap door helps contain debris and achieves

finer sizing (optional)

Hydraulic piston motor

Gear motor



Belt transmission
Bulkhead for hydraulic connections
Rear hood with mechanical adjustment
Rotor Bite Limiter
Dedicated rear hood (deflector)

Fixed thumb bracket
Customized attachment bracket with pins
Multiple tooth options
Case drain required

BL1/EX/VT-75	BL1/EX-75
17-37	16-24
2600-5080	2610-3625
4-7.5	4.5-7.5
31	31
860	849
12.2	12.2
5	5
14	14