

## FORESTRY MULCHERS FOR SKID STEERS

# PMM/SSL

### Brush mulcher with hammer/flail rotor for skid steers.

A universal mulcher suitable for mulching saplings bushes, crop residues and grass. Thanks to its "floating system", the mulcher's rotor adheres perfectly to the terrain, ensuring a homogeneous material after mulching. The support roller, larger in comparison to other attachments, guarantees the best performance

even on particularly damp terrain. The machine can be equipped with hammers for mulching material up to 8 cm diameter or grass flail to better respond to the various needs of the customer.



60-100 hp



Ø 8 cm max



**Steel counter-blades** helps mulch material into a smaller final size



**Self leveling protection flaps**



**Attachment plate with self leveling device** adapts to all types of terrain



**Self cleaning rear roller with integrated skids**



#### STANDARD EQUIPMENT

32/65cc variable manual displacement hydraulic piston motor with relief and anticavitation valve	Self levelling protection flaps
Motor enclosed in the frame	Supporting service leg
Belt transmission	Welded counterblades
Hydraulic hoses	Self cleaning rear roller with integrated skids
Front hood with mechanical adjustment	Attachment plate with self levelling device
Adjustable skids	

#### OPTIONS

Customized setting hydraulic motor	Possibility to have the rotor equipped with PML hammers or Y-flail
Stronger bearing for back roller	

MODEL	PMM/SSL-175	PMM/SSL-200
<b>Engine</b> (hp)	60-100	70-100
<b>Flow rate</b> (L/min)	56-125	56-125
<b>Pressure</b> (bar)	180-250	180-250
<b>Working width</b> (mm)	1780	2020
<b>Total width</b> (mm)	2000	2180
<b>Weight</b> (kg)	850	910
<b>Rotor diameter</b> (mm)	440	440
<b>Max shredding diameter</b> (mm)	80	80
<b>No. hammers</b> type PMM	22	24
<b>No. flail</b> type Y/3	22	24

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

#### MAIN OPTIONS



Multiple flail



HAMMER PMM (standard)



FLAIL Y/3 (option)