STUMP CUTTERS FOR EXCAVATORS

SCL/EX

Stump cutter for excavators from 7 to 15 t.

The SCL/EX is for excavators ranging from 7 to 15 t. Thanks to the heavy duty and larger disk, stump removal is made easier in any situation; even when using medium and small size excavators. This unit is compact, high performing and is equipped with a hydraulic door to control the exit of debris.

105-170 L/min

7-15 t



Access panel

VT motor
adjustable motor to obtain the maximum performance from any excavator, protected from dirt and damage

Front hydraulic hood with bolt-on chains

Motor enclosed in frame
protected from dirt and damage

Adjustable supporting service stand
for storing the machine when not in use

MAIN OPTIONS

Front fixed thumb

Customized setting hydraulic motor



Customized attachment bracket with fixed thumb

Customized attachment bracket

STANDARD EQUIPMENT	
110/60cc variable torque hydraulic piston motor (105-170 L/min)	Poly Chain® belt transmission
Flow control system valve	Bulkhead for hydraulic connections
Safety and anticavitation valve	Hydraulic front hood
Enclosed / anti dust machine body	Screwed protection chains
Motor enclosed in the frame	Supporting service leg

OPTIONS	
80/50cc variable torque hydraulic piston motor (75-120 L/min)	Front fixed thumb bracked
Customized setting hydraulic motor	Customized attachment bracket with pins
Diverter valve (plug & play)	Customized attachment bracket with pins and leg

MODEL	SCL/EX/VT
Flow rate (L/min)	105-170
Pressure (bar)	180-350
Excavator weight (t)	7-15
Total width (mm)	902
Weight (kg)	755
Rotor diameter (mm)	660
No. teeth type L/1+L/2	15+15

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

DISC ROTOR

TOOTH L/1
(standard)

TOOTH L/2
(standard)