FORESTRY MULCHERS FOR EXCAVATORS

UML/HY/RW - FML/HY/RW

Mulcher for excavators from 6 to 10 t.

The UML/HY/RW mulcher has been specifically designed for railway vehicles or other special machines. It is ideal for maintaining areas that are difficult to reach such as the embankments of railway lines.

The optimum weight, light frame and oversized rotor equipped with fixed teeth, allows for the mulching of material up to 5 in diameter. It will mulch even with the presence of stones or rocks found near railroads.

17-48 gal/min

Ø 5 in max

6-10 t

Steel counter-blades
helps mulch material into a smaller final size

Hydraulic piston motor 63cc with relief and anticavitation valve

Motor enclosed in frame
protected from dirt and damage

Swinging hammer rotor
(FML/HY/RW)

MAIN OPTIONS

Rotor with Bite Limiter technology
maximum productivity using the least amount of power

Customized setting hydraulic motor

STANDARD EQUIPMENT

32/65cc variable manual displacement hydraulic piston motor (24-48 gpm) (UML/HY/RW - FML/HY/RW)	Belt transmission
55/38cc variable torque hydraulic piston motor (24-36 gpm) (UML/HY/RW/VT)	Bulkhead for hydraulic connections
Flow control system valve	Hydraulic rear hood
Safety and anticavitation valve	Screwed protection chains
Enclosed / anti dust machine body	Welded counterblades
Motor enclosed in the frame	

OPTIONS

Customized setting hydraulic motor	Multiple tooth options
Rotor Bite Limiter	
Not supplied with hoses	Case drain required

MODEL	UML/HY/RW-125	UML/HY/RW-150	UML/HY/RW/VT-125	UML/HY/RW/VT-150	FML/HY/RW-125	FML/HY/RW-150
Flow rate (gal/min)	24-48	24-48	24-36	24-36	17-44	17-44
Pressure (PSI)	3200-5100	3200-5100	3200-5100	3200-5100	3200-5100	3200-5100
Excavator weight (t)	6-10	6-10	6-10	6-10	6-10	6-10
Working width (in)	53	62	53	62	53	62
Weight (lbs)	1499	1653	1499	1653	1213	1301
Rotor diameter (in)	16.7	16.7	16.7	16.7	16.7	16.7
Max shredding diameter (in)	5	5	5	5	5	5
No. teeth type C/3+C/3/SS	26+2	32+2	26+2	32+2	-	-
type I+C/3/SS	36+2	42+2	36+2	42+2	-	-
No. hammers type FML	-	-	-	-	20	24

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions.
The technical data in this catalogue may be altered without prior notice.

ROTOR TYPE C

C/3
(standard)

C/3/HD
(option)

BL BLADE
(option)

ROTOR TYPE BL

BL BLADE
(option)

ROTOR TYPE I

I
(option)

C/3/SS
(side scraper)

HAMMER FML
(standard)