

FORESTRY TILLERS FOR SPECIAL VEHICLES

200/S

Universal hydraulic tiller for higher horse power carriers.

The 200/S is lightweight and comes in different widths, making it perfect for a wide range of vehicles. The gear drive lets the rotor work at a slower speed than conventional belt-driven forestry mulchers.



250-300 hp



Ø 12 in max



Depth 12 in




Customized attachment plate (optional)

Hydraulically controlled hood
to adjust final product size

180 cc hydraulic motor

Dual transmission with side gearbox



STANDARD EQUIPMENT

Considering the various available options and high level of customization, the final configuration will be specified upon request.

MODEL	200/S 225	200/S 250
Engine (hp)	250-300	250-300
Flow rate (gal/min)	94-108	94-108
Pressure (PSI)	4600-5800	4600-5800
Working width (in)	91	101
Total width (in)	105	114
Weight (lbs)	6971	7496
Rotor diameter (in)	23.2	23.2
Max working depth (in)	12	12
Max shredding diameter (in)	12	12
No. teeth type B/3+C/3/SS	82+4	96+4

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions.
The technical data in this catalogue may be altered without prior notice.

ROTOR TYPE B



B/3
(standard)



G/3
(option)



G/3/HD
(option)



C/3/SS
(side scraper)