

STONE CRUSHERS

# RSH/HP

FAE's top-of-the-line stone crushers.

RSH/HP is FAE's most advanced stone crusher. It is suiting for crushing slabs of rock and stones up to 20 in in diameter and 20 in deep. It works with 360-500 hp tractors and has a working width of 80-100 in. RSH/HP is made for difficult farmland clearing work in places where large rocks and stones need to be cleared to prepare the field for agricultural use.

Its wide opening guides large material towards the rotor and, in combination with the adjustable counterblade, helps maintain consistently high performance when working the soil.




**Structural frame in steel**  
maximum strength and durability  
in heavy duty operations

**Interchangeable  
Hardox® anti wear plates**  
quick and easy maintenance



**Side reduction gears and central  
gearbox with oilcooling system**  
maximum productivity and efficiency  
maintained in all workingconditions



**Wide opening**  
to efficiently process more material

## MAIN OPTIONS



**Rear hood grill**  
allows larger material to be  
held back and crushed again  
for optimum results



**Adjustable steel  
dosing blade**  
perfect distribution  
of the crushed material



**Hydraulic top link**  
for an optimal working  
depth control



360-500 hp



Ø 20 in max (stones)



Depth 20 in



### STANDARD EQUIPMENT

Hydraulic rear hood	Gearbox with freewheel
Interchangeable inner antiwear plates in Hardox®	Gearbox with oil cooling system
Enclosed machine body	PTO shaft
Inside lateral protection	Friction clutches
Protection chains	Bolted-on rotor shafts (in forged steel)
Transmission with side gearbox	Adjustable Hardox® counter-blade
Side gearbox with oil cooling system	Penetration skids

### OPTIONS

Bolted grid on rear hood	Hydraulic top link
Multiple tooth options	Dozing blade
IVT - CVT or creeper transmission mandatory	Forestry tires and carrier belly pan strongly recommended

MODEL		RSH/HP 200	RSH/HP 225	RSH/HP 250
	Engine (hp)	360-500	360-500	360-500
	PTO (rpm)	1000	1000	1000
	Working width (in)	83	92	102
	Total width (in)	105	115	124
	Weight (lbs)	15543	16424	17306
	Max shredding diameter (in)	20	20	20
	Max working depth (in)	20	20	20
ROTOR G/3	Rotor diameter (in)	43.1	43.1	43.1
	No. teeth type G/3	104	116	132
	type STC/3/FP+STC/FP	4+4	4+4	4+4
ROTOR 65	Rotor diameter (in)	41.9	41.9	41.9
	No. teeth type R+R/HD	138+24	160+24	182+24
	type STC/3/FP+STC/FP	6+6	6+6	6+6

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

### ROTOR TYPE G



**G/3**  
(standard)



**G/3/HD**  
(option)



**R 65**  
(option)



**R/HD 65**  
(option)

### ROTOR TYPE R



**STC/3/FP**  
(side scraper)



**STC/FP**  
(side scraper)