FORESTRY MULCHERS FOR SKID STEERS

BL4/SSL/VT - BL4/SSL/SONIC

Forestry mulcher for skid steers up to 135 hp.

The BL4/SSL forestry mulcher, designed for Skid steers from 90 to 135 hp and is able to shred material up to 12" in diameter. Thanks to the Bite Limiter technology this head is ideal to have high productivity in vegetation management and provide high and efficient shredding in wooded and forestry areas. The head is designed

to offer high productivity, durability and ease of maintenance for the operator. The BL4/SSL is available in VT version or with Sonic, a FAE exclusive technology that optimize that optimizes performance and can be easily calibrated using the dedicated FAE App for smartphone.



Interchangeable inner anti-wear plate

high relialibility and easy replacement

Low profile frame

designed for highest working visibility

Rotor with Bite Limiter technology

maximum productivity using the least amount of power thanks to special wear-resistant steel limiters and blades type BL/MAX



Sonic technology

new automatic intelligent system that manages the hydraulic transmission that provides the maximum shredding capacity in all conditions



VT Motor (Variable Torque)

with automatic torque boost

Hydralic Quick Couplers

Flat face quick couplers to allow a Plug & Play coupling with the most popular skid steers



MAIN OPTIONS



Customized VT motor setting

Customized motor setting to obtain the maximum performance out of any hydraulic system



Wiring adaptors

Wiring adaptors
Wiring adaptors interface
to allows a Plug & Play coupling
with the most popular skid
steers



Roof Mounted cooler kit

High performance hydraulic oil cooling system to assemble on the skid steer roof



Sonic System



90-135 hp



Ø 12 in max



STANDARD EQUIPMENT

107 cc VT hydraulic piston motor variable displacement (BL4/SSL/VT)	Bite Limiter rotor
107 cc Sonic hydraulic piston motor electronic control (BL4/SSL/SONIC)	Interchangeable flat steel counter blades
Anti-shock block valve with relief and anti-cavitation valves	Sonic System (BL4/SSL/SONIC)
Poly Chain® belt transmission	Hydraulic hoses for connections
Enclosed / anti-dust machine body	Mechanical adjustable guard frame
Motor enclosed in the frame	Interchangeable protection chains
Interchangeable inner anti-wear plate in Hardox®	Interchangeable and adjustable support skids
Interchangeable forged steel rotor shafts	

OPTIONS

OFTIONS				
Customized setting hydraulic motor (BL4/SSL/VT)	Roof mounted cooler kit			
Adaptor wiring (BL4/SSL/SONIC)				

Case drain required

MODEL	BL4/SSL/VT 150	BL4/SSL/SONIC 150	BL4/SSL/VT 175	BL4/SSL/SONIC 175
Power (hp)	90-135	90-135	90-135	90-135
Flow rate (gal/min)	32-45	32-45	32-45	32-45
Pressure (PSI)	3500-5080	3500-5080	3500-5080	3500-5080
Working width (in)	62	62	72	72
Total width (in)	75	75	84	84
Weight (lbs)	2822	2822	3020	3020
Rotor diameter (in)	18.3	18.3	18.3	18.3
Max shredding diameter (in)	12	12	12	12
No. blade type BL/MAX	26	26	32	32

*Variable displacement hydraulic motor.

ROTOR TYPE BL



BLADE BL/MAX (standard)

